

US009908305B2

# (12) United States Patent

#### Chamberlain et al.

## (54) FIBER ARCHITECTURE OPTIMIZATION FOR CERAMIC MATRIX COMPOSITES

(71) Applicant: Rolls-Royce Corporation, Indianapolis, IN (US)

IN (US)

(72) Inventors: Adam L. Chamberlain, Mooresville,

IN (US); Andrew J. Lazur, Huntington

Beach, CA (US)

(73) Assignee: Rolls-Royce Corporation, Indianapolis,

IN (US)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 617 days.

(21) Appl. No.: 14/208,407

(22) Filed: Mar. 13, 2014

(65) **Prior Publication Data** 

US 2016/0136925 A1 May 19, 2016

### Related U.S. Application Data

- (60) Provisional application No. 61/799,241, filed on Mar. 15, 2013.
- (51) Int. Cl.

  B32B 5/12 (2006.01)

  B32B 18/00 (2006.01)

  C04B 35/80 (2006.01)

  B32B 5/02 (2006.01)
- (52) U.S. Cl.

## (10) Patent No.: US 9,908,305 B2

(45) **Date of Patent:** Mar. 6, 2018

2235/5248 (2013.01); C04B 2235/5256 (2013.01); C04B 2235/5268 (2013.01)

## (58) Field of Classification Search

CPC .. B32B 5/02; B32B 5/024; B32B 5/12; B32B 2260/00; B32B 2260/023; B32B 2260/04 See application file for complete search history.

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

5,141,775	A		8/1992	Patrigeon et al.
5,154,948	Α		10/1992	Patrigeon et al.
5,348,056	A	*	9/1994	Tsuzuki B29C 70/24
				139/11

#### (Continued)

#### FOREIGN PATENT DOCUMENTS

EP 1215183 A1 4/2009

#### OTHER PUBLICATIONS

U.S. Appl. No. 61/799,241 by Chamberlain et al., entitled "Fiber Architecture Optimization for Improved Infiltration of SIC Based Ceramic Matrix Composites," filed Mar. 15, 2013.

(Continued)

Primary Examiner — Jacob Cigna (74) Attorney, Agent, or Firm — Brinks Gilson & Lione

#### (57) ABSTRACT

Creating a ceramic matrix structure may include alternating different layers of fiber fabric to achieve porosity, infiltration, and/or other objectives. Different layers of the ceramic matrix structure may be configured differently to achieve different objectives in different regions of the ceramic matrix structure. The fiber tow spacing, fiber count and/or other characteristics may be varied within individual layers and/or among different layers of the ceramic matrix structure.

## 7 Claims, 7 Drawing Sheets

